

# 2.5mm Video Banners



<b>Pixel configuration</b>	<b>SMD2020</b>
Pixel Pitch (mm)	2.571
Pixel Matrix per Panel (dots)	112 × 84
Display Resolution( W X H )(Pixel)	224 × 756
Pixel Density (dots /screen)	169344
Module size (W x H x D) /(mm)	288 × 216 × 6.7
Panel Dimension (W x H x D) /(mm)	576 × 1944 × 35
Panel Material	Aluminum / 10 colors options
Body Module Composition ( W x H )	2*9
Screen the Weight (kg/screen)	35kg /screen
Module Weight ( Single-mode group / kg )	0.4 Kg
Color Depth (Bit)	14 bit
Gray Scale	16384
Refresh Rate ( Hz)	3840 HZ
Driver Method /scan	Scan 1/28
Brightness ( nits)	600-1200 nits, adjustable( 8levels )
Horizontal/ Vertical Viewing Angel( H/V°)	H/160° V/160°
AC Power input ( V )	AC 110V~ 220V ±10%
AC Power Frequency ( Hz)	50Hz/60Hz
Max. Power (W/screen)	683 W/screen
Avg. Power (W/screen)	228 W/screen
Storage Temp (°C)	-10 °C -- +60°C
Operation Temperature (°C)	0°C -- +50°C
Storage Humidity ( RH)	10%~90% no frost and dew
Operating Humidity( RH)	10%~90% no frost and dew
Product Protection grade	Front IP30 , Back IP30
LED Lifetime ( hrs)	≥ 100000
Installation Type	Wall Hanging 、 stacking 、 Hanging
Maintenance Method	Front service